



50 Hz WITHSTAND VOLTAGE, WET : 50 kV
 1.2/50 IMPULSE VOLTAGE WITHSTAND : 125 kV
 MIN BENDING LOAD : 12.5 kN
 CREEPAGE DISTANCE, MIN : 800 mm
 WEIGHT : 2.7 kg

Rev. No.	Drwg. modification	Date/sign.
B	Re-designed	16.01.2015/SOB.
A	First issue. Re-designed	26.06.2014/SOB.

Pos	Designation	Mr. Reference	Material	Remarks
4	Glassfiber Rod	Mr. Reference	EGR-Glass	
3	Top-Clamp fitting	A40100 01	AA6082-T6	Aluminium special threaded
2	Pin-fitting	A40111 01	AA6082-T6	Aluminium special threaded
1	Sheds	Mr. Reference	HTV Silicone	Colour: Red

24kV LINE POST INSULATOR
CLP-24-TKA-170

Scale	1:2
Design	S. Bluskoven 26.06.2014
Approved	R. Johnsmassen 26.06.2014

Art.No.	K35001 01	Ref.	NTP PRODUCTS AS NORWAY	Supersedes	A 3	CD-File	K 35001 01 B
---------	-----------	------	---------------------------	------------	-----	---------	--------------

THIS DRAWING IS THE PROPERTY OF NTP AND MUST NOT BE COPIED WITHOUT OUR WRITTEN PERMISSION. THE CONTENTS THEREOF MUST NOT BE DISCLOSED TO A THIRD PARTY NOR BE USED FOR ANY UNAUTHORIZED PURPOSE. © NTP AS